





Self-Propelled Scissor Lifts

GS™-2032, GS-2632 & GS-3232

Specifications



Models	GS-2032	
Measurements	US	Metric
Working height maximum*	26 ft	7.9 m
▲ Platform height maximum	29 ft	6.10 m
▲ Platform height stowed	3 ft 4.5 in	1.03 m
▲ Platform length - outside	7 ft 5 in	2.26 m
▲ Platform length - outside extended	10 ft 5 in	3.18 m
Side-out platform extension deck	3 ft	0.91 m
▲ Platform width - outside	2 ft 8 in	0.81 m
Guardrail height: fixed rails	3 ft 3 in	0.99 m
fold down rails (CE)	3 ft 7 in	1.10 m
Toeboard height	6 in	0.15 m
▲ Height - stowed		
fixed rails	6 ft 6 in	2.03 m
folding guardrails (CE)	7 ft	2.13 m
rails folded	5 ft 9 in	1.75 m
▲ Length - stowed	8 ft	2.44 m
Length - extended	10 ft 11 in	3.33 m
▲ Width	2 ft 8 in	0.81 m
▲ Wheelbase	6 ft 1 in	1.85 m
▲ Ground clearance - center	3.5 in	89 mm
▲ - with pothole guards deployed	0.88 in	22 cm

Productivity

Maximum platform occupancy**	2	2
Lift capacity	800 lbs	363 kg
Extension deck capacity	250 lbs	113 kg
Drive height	full height	
Drive speed - stowed	2.2 mph	3.5 km/h
Drive speed - raised	0.5 mph	0.8 km/h
Gradeability - stowed***	30%	
Maximum outrigger leveling:		
front to back	_____	_____
Maximum outrigger leveling:		
side to side	_____	_____
Turning radius - inside	zero	zero
Turning radius - outside	7 ft	2.13 m
Raise / lower speed	28 / 24 sec	28 / 24 sec
Controls	proportional	
Drive	dual front wheel	
Multiple disc brakes	dual rear wheel	
Tires - solid non-marking	15 x 5 in	38 x 13 cm

Power

Power source	24 V DC	
	(four 6V 225 Ah batteries)	
Hydraulic system capacity	4.5 gal	17 L

Weight****

ANSI, CSA	3,574 lbs	1,621 kg
CE, AUS	4,024 lbs	1,825 kg

Standards Compliance ANSI A92.6, CSA B354.2, CE Compliance, AS 1418.10

* The metric equivalent of working height adds 2 m to platform height. U.S. adds 6 ft to platform height.
 ** CE/AUS markets: GS-2632 and GS-3232 indoor use only. GS-2032 outdoor use-one person maximum occupancy.
 *** Gradeability applies to driving on slopes. See operator's manual for details regarding slope ratings.
 **** Weight will vary depending on options and/or country standards.



Self-Propelled Scissor Lifts

GS™-2032, GS-2632 & GS-3232

Features

Standard Features

Measurements

GS-2032

- 26 ft (8.10 m) working height
- Up to 800 lbs (363 kg) lift capacity

Productivity

- 89 x 32 in (2.26 x .81 m) steel platform
- 36 in (.91 m) extension deck
- Fixed rail with chain entry gate (standard GS™-2032)
- Folding rails with half-height swing gate (standard on all CE, GS™-2632, GS™-3232)
- Automatic leveling outriggers (GS™-3232 only)
- Dual front wheel drive
- Universal 20 amp smart charger
- Rear recessed charger receptacle
- SmartLink™ - proportional lift and drive
- Platform control with battery charge indicator and diagnostic display
- On-board diagnostic system
- AC power to platform
- Lanyard attachment points
- Manual platform lowering valve
- Emergency stop at both platform and ground controls
- Rear wheel multiple disc brakes
- Front wheel hydraulic dynamic braking
- Brake release
- Swing-out component trays
- Solid non-marking tires
- Pothole guards
- Tilt level sensor with audible alarm
- Descent alarm
- Electronic horn
- Hour meter

Power

- 24 V DC (four 6 V 225 Ah batteries)

Options & Accessories

Productivity Options

- Folding rails with half-height swing gate (GS™-2032)
- Platform swing gate, half-height (GS™-2032)
- Air line to platform
- Dual flashing beacons
- Motion alarm
- Automotive horn
- Biodegradable hydraulic fluid

Power Options

- Power inverter (120 V/60 Hz)
- EE rating
- AGM maintenance-free batteries



Genie United States

6464 185th Ave. NE
Redmond, WA 98052
Telephone +1 (425) 881-1800
Toll Free in USA/Canada +1 (800)-536-1800
Fax +1 (425) 883-3475

Distributed By:



Effective Date: January, 2016. Product specifications and prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and site and we make no other warranty, express or implied. Products and services listed may be trademarks, service marks or trade names of Terex Corporation and/or their subsidiaries in the USA and many other countries. Terex, Genie and AWP are registered trademarks of Terex Corporation or its subsidiaries. © 2016 Terex Corporation.

0632 0210, Part No. 106376

www.genielift.com